

IH126K Phenolic Insulation Block 25 mm Thick

(D 10 15)

for steel, copper and plastic pipe 15 - 219 mm



Features and benefits

- load bearing insulation ring for steel, copper and plastic pipe
- metal spreader plate above 50 NB
- foil covered
- manufactured from High Density Phenolic Foam
- negligible water absorption
- does not contain CFC's and HCFC's
- K value 0.030 to 0.032 W/m C at 10 °C
- density: <111mm OD pipe, 60kgs/m³
- density: 111mm to 169mm OD pipe, 80kgs/m³
- temperature resistance from -50 °C to +110 °C
- Class 'O' to BS476/7
- ignitability BS476 Pt5, Class 'P'
- 5% smoke emission to BS 5111



Part No.	D (mm)	DN	Pack 1
8901025015	15	-	50
8901025021	21 - 22	15	25
8901025027	27 - 28	20	25
8901025034	34 - 35	25	25
8901025042	42	32	25
8911025048	48	40	50
8911025054	54	-	50
8911025060	60	50	5
8911025066	66	-	5
8911025076	76	65	5
8911025089	89	80	25
8911025108	108	-	5
8911025114	114	100	5
8911025133	133	-	15
8911025140	140	125	14
8911025159	159	-	5
8911225168	168	150	3
8911225219	219	200	4