

IH126K Phenolic Insulation Block 40 mm Thick

(D 10 25)

for steel, copper and plastic pipe 15 - 273 mm



Features and benefits

- load bearing insulation ring for steel, copper and plastic pipe
- metal spreader plate above 50 NB
- foil covered
- manufactured from High Density Phenolic Foam
- negligible water absorption
- does not contain CFC's and HCFC's
- K value 0.030 to 0.032 W/m C at 10 °C
- density: <111mm OD pipe, 60kgs/m³
- density: 111mm to 169mm OD pipe, 80kgs/m³
- density: >170mm OD pipe, 120kgs/m³
- temperature resistance from -50 °C to +110 °C
- Class 'O' to BS476/7
- ignitability BS476 Pt5, Class 'P'
- 5% smoke emission to BS 5111



| Part No. | D (mm) | DN | Pack 1 |
|------------|-----------|-----|--------|
| 8901040015 | 15 | - | 50 |
| 8901040021 | 21 - 22 | 15 | 50 |
| 8901040027 | 27 - 28 | 20 | 50 |
| 8901040034 | 34 - 35 | 25 | 25 |
| 8901040042 | 42 | 32 | 5 |
| 8911040048 | 48 | 40 | 5 |
| 8911040054 | 54 | - | 25 |
| 8911040060 | 60 | 50 | 25 |
| 8911040066 | 66 | - | 25 |
| 8911040076 | 76 | 65 | 5 |
| 8911040089 | 89 | 80 | 3 |
| 8911040108 | 108 | - | 5 |
| 8911040114 | 114 | 100 | 3 |
| 8911040133 | 133 | - | - |
| 8911040140 | 140 | 125 | 3 |
| 8911040159 | 159 | - | 5 |
| 8911240168 | 168 | 150 | 6 |
| 8911240219 | 219 | 200 | 2 |
| 8911240273 | 273 | 250 | 2 |